

- 所有項目會先以灰色出現，點擊滑鼠後再逐一highlight, shake選項則會再加上晃動效果 □
style="padding-top: 3em;" 則是與前一項目的行距

```
<div class="blindDown" style="padding-top: 0.5em;">
<ul class="incremental show-first" >
<li>sss</li>
<li class="shake">An even scriptaculous effects using presentacular, by Jose
Manuel Caicedo!</li>
</ul>
</div>
```

- 增加音樂效果(暫不需要)

```
<!-- Use this code to add music/voice to a given slice -->
<object data="http://conga.oan.es/%7Ealonso/club.mp3" archive="volume:100"
type="audio/mp3" width="0" height="0" class="handout"></object>
```

- 在分隔線後的部份為note
- 可以給每張投影片一這獨立於標題外的描述以及自動切換的時間

```
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
sectionNames["6"] = "End";
// Section times here, with transparency number and delay in seconds
sectionTimes["1"] = "20";
sectionTimes["2"] = "15";
sectionTimes["4"] = "5";
</script>
```

- 可以給每張投影片一這獨立於標題外的描述以及自動切換的時間

```
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
```

```
sectionNames["6"] = "End";  
// Section times here, with transparency number and delay in seconds  
sectionTimes["1"] = "20";  
sectionTimes["2"] = "15";  
sectionTimes["4"] = "5";  
</script>
```

- 可以設定右下角footer的部份

```
<script language="javascript">  
var foodiv;  
if (document.getElementById) {  
    foodiv = document.getElementById('footer');  
} else {  
    foodiv = document.footer;  
}  
foodiv.innerHTML += '<h3>Jun Wu, CSIE, NPIC; September 15, 2013</h3>';  
</script>
```

還有更多

```
~~SLIDESHOW thesis~~  
  
===== S5 Reloaded投影片製作測試 =====  
  
只有主標題，副標題要用HTML  
S5 Reloaded plugin for DokuWiki, with Scriptaculous  
<HTML>  
<HR>  
</HTML>  
  
Jun Wu  
CSIE@NPU  
  
<HTML><HR></HTML>  
http://conga.oan.es/~alonso/doku.php?id=s5reloadedTest  
  
Code for this presentation: http://conga.oan.es/~alonso/s5reloadedtest.txt  
  
===== Features =====  
<HTML>  
<div class="blindDown" style="padding-top: 0.5em;">  
<ul class="incremental show-first" >  
<li>dddd</li>  
<li>Intedd</li>  
<li class="shake">An even scriptaculous effects using presentacular, by Jose  
Manuel Caicedo!</li>  
</ul>
```

```
</div>
</HTML>
```

And all these features can be used from DokuWiki. Let's see some of them.

```
<HTML>
<!-- Use this code to add music/voice to a given slice -->
<object data="http://conga.oan.es/%7Ealonso/club.mp3" archive="volume:100"
type="audio/mp3" width="0" height="0" class="handout"></object>
</HTML>
```

```
-----
```

First note for this slice

Second note

```
===== Scalable images =====
```

```
<HTML>
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
sectionNames["6"] = "End";
// Section times here, with transparency number and delay in seconds
sectionTimes["1"] = "20";
sectionTimes["2"] = "15";
sectionTimes["4"] = "5";
// Now let's modify the wiki name + presentation date. Is ugly to have here
to date
// and time by default. Note that in the css the slide h2 section is hidden
and a
// slide h3 is included to properly show the information I will include now
here.
// First I get the footer div and then I modify its html code.
var foodiv;
if (document.getElementById) {
    foodiv = document.getElementById('footer');
} else {
    foodiv = document.footer;
}
foodiv.innerHTML += '<h3>Tom 獺 Alonso - OAN &#8226; July 22, 2010</h3>';
</script>
```

</HTML>

Images are shown with class="scale" by default, and this applies always unless you only specify width OR height in the image link. Resize the window to see how the images are scaled.

```
{{:236084main_milkyway-full-annotated.jpg?540x540 |}}
{{ :bhr71.jpg?280x310|}}
{{ :pleyades.png?280x230|}}
```

First note for this slice

Second note

===== Effects using HTML tag code =====

```
<HTML><div class="grow_2" style="padding-top: 1em;">Effects in lists
requires to use the HTML tag in DokuWiki, but this is quite easy and you
don't have to write a lot. This text will grow and appear in 2
second.</div></HTML>
```

<HTML>

```
<ul class="incremental show-first">
<li class="pulsate_0.4">Pulsate this first point, and remove subpoints in 3
seconds forever</li>
  <ul class="fold_3">
    <li>Subpoint 1</li>
    <li>Subpoint 2</li>
    <li>Subpoint 3</li>
  </ul>
<li style="display:none" class="appear_4">Second point, everything appear
progressively</li>
<li class="fade_4">Third point, everything disappear progressively. You will
never see this again.
  <ul>
    <li>Subpoint 1</li>
    <li>Subpoint 2</li>
    <li>Subpoint 3</li>
  </ul>
</li>
</ul>
</HTML>
```

<HTML>

```
<p><span class="">We can also display</span> <span class="">one</span> <span
class="">word</span> <span class="current">at</span> <span
class="incremental">a</span> <span class="incremental">time,</span>
<span class="incremental">or a phrase</span> <span class="incremental">at a
```


