- 所有項目會先以灰色出現，點擊滑鼠後再逐一highlight, shake選項則會再加上晃動效果 style="padding-top: 3em;" 則是與前一項目的行距

```
<div class="blindDown" style="padding-top: 0.5em;">
<ul class="incremental show-first" >
<li>sss</li>
<li class="shake">An even scriptaculous effects using presentacular, by Jose Manuel Caicedo!</li>
</ul>
</div>
```

- 增加音樂效果(暫不需要)

```
<!-- Use this code to add music/voice to a given slice -->
<object data="http://conga.oan.es/%7Ealonso/club.mp3" archive="volume:100" type="audio/mp3" width="0" height="0" class="handout"></object>
```

- 在分隔線後的部份為note
- 可以給每張投影片一這獨立於標題外的描述以及自動切換的時間

```
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
sectionNames["6"] = "End";
// Section times here, with transparency number and delay in seconds
sectionTimes["1"] = "20";
sectionTimes["2"] = "15";
sectionTimes["4"] = "5";
</script>
```

- 可以給每張投影片一這獨立於標題外的描述以及自動切換的時間

```
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
```

```
sectionNames["6"] = "End";
// Section times here, with transparency number and delay in seconds
sectionTimes["1"] = "20";
sectionTimes["2"] = "15";
sectionTimes["4"] = "5";
</script>
```

- 可以設定右下角footer的部份

```
<script language="javascript">
var foodiv;
if (document.getElementById) {
    foodiv = document.getElementById('footer');
} else {
    foodiv = document.footer;
}
foodiv.innerHTML += '<h3>Jun Wu, CSIE, NPIC; September 15, 2013</h3>';
</script>
```

還有更多

```
~~SLIDESHOW thesis~~

====== S5 Reloaded投影片製作測試 ======

只有主標題, 副標題要用HTML
S5 Reloaded plugin for DokuWiki, with Scriptaculous
<HTML>
<HR>
</HTML>

Jun Wu
CSIE@NPU

<HTML><HR></HTML>
http://conga.oan.es/~alonso/doku.php?id=s5reloadedTest

Code for this presentation: http://conga.oan.es/~alonso/s5reloadedtest.txt

===== Features =====
<HTML>
<div class="blindDown" style="padding-top: 0.5em;">
<ul class="incremental show-first" >
<li>dddd</li>
<li>Intedd</li>
<li class="shake">An even scriptaculous effects using presentacular, by Jose
Manuel Caicedo!</li>
</ul>
```

```
</div>
</HTML>


And all these features can be used from DokuWiki. Let's see some of them.

<HTML>
<!-- Use this code to add music/voice to a given slice -->
<object data="http://conga.oan.es/%7Ealonso/club.mp3" archive="volume:100"
type="audio/mp3" width="0" height="0" class="handout"></object>
</HTML>

----

First note for this slice

Second note


===== Scalable images ======

<HTML>
<!-- Set meta parameter autoMatic to true to enable automatic play-->
<meta name="autoMatic" content="true" />
<script language="javascript">
// Section names here, with transparency number and description
sectionNames["1"] = "Introduction to this plugin";
sectionNames["2"] = "Details";
sectionNames["5"] = "Compatibility";
sectionNames["6"] = "End";
// Section times here, with transparency number and delay in seconds
sectionTimes["1"] = "20";
sectionTimes["2"] = "15";
sectionTimes["4"] = "5";
// Now let's modify the wiki name + presentation date. Is ugly to have here
to date
// and time by default. Note that in the css the slide h2 section is hidden
and a
// slide h3 is included to properly show the information I will include now
here.
// First I get the footer div and then I modify its html code.
var foodiv;
if (document.getElementById) {
    foodiv = document.getElementById('footer');
} else {
    foodiv = document.footer;
}
foodiv.innerHTML += '<h3>Tom獺s Alonso - OAN &#8226; July 22, 2010</h3>';
</script>
```

```
</HTML>

Images are shown with class="scale" by default, and this applies always
unless you only specify width OR height in the image link. Resize the window
to see how the images are scaled.

{{:236084main_milkyway-full-annotated.jpg?540x540 |}}
{{ :bhr71.jpg?280x310|}}
{{ :pleyades.png?280x230|}}

----

First note for this slice

Second note

===== Effects using HTML tag code =====

<HTML><div class="grow_2" style="padding-top: 1em;">Effects in lists
requires to use the HTML tag in DokuWiki, but this is quite easy and you
don't have to write a lot. This text will grow and appear in 2
second.</div></HTML>

<HTML>

<ul class="incremental show-first">
<li class="pulsate_0.4">Pulsate this first point, and remove subpoints in 3
seconds forever</li>
  <ul class="fold_3">
   <li>Subpoint 1</li>
   <li>Subpoint 2</li>
   <li>Subpoint 3</li>
  </ul>
<li style="display:none" class="appear_4">Second point, everything appear
progresively</li>
<li class="fade_4">Third point, everything disappear progresively. You will
never see this again.
  <ul>
   <li>Subpoint 1</li>
   <li>Subpoint 2</li>
   <li>Subpoint 3</li>
  </ul>
</li>
</ul>
</HTML>

<HTML>
<p><span class="">We can also display</span> <span class="">one</span> <span
class="">word</span> <span class="current">at</span> <span
class="incremental">a</span> <span class="incremental">time,</span>
<span class="incremental">or a phrase</span> <span class="incremental">at a
```

```
time,</span>
<span class="incremental">or even</span> <span
class="incremental">o</span><span class="incremental">n</span><span
class="incremental">e</span> <span class="incremental">l</span><span
class="incremental">e</span><span class="incremental">t</span><span
class="incremental">t</span><span class="incremental">e</span><span
class="incremental">r</span> <span class="incremental">at a time!</span></p>
<p><span class="incremental">(But HTML code is not very clean)</span></p>
</HTML>

===== Available effects =====

In most of them you can control the duration of the effect. See
scriptaculous for reference.

  * blinddown: Effect.BlindDown, blindup: Effect.BlindUp
  * puff: Effect.Puff, highlight: Effect.Highlight
  * shake: Effect.Shake, pulsate: Effect.Pulsate
  * slidedown: Effect.SlideDown, slideup: Effect.SlideUp
  * grow: Effect.Grow, shrink: Effect.Shrink
  * fade: Effect.Fade, appear: Effect.Appear
  * fold: Effect.Fold, dropout: Effect.DropOut
  * switchoff: Effect.SwitchOff, squish: Effect.Squish

===== Compatibility with other plugins =====

You can use also other plugins to show tables, formulae (asciimath), or tips
(wrap).

<WRAP tip 180px right>
//**My tip**//
This is my tip
</WRAP>
^    My table           ^^^
| Row 1 Col 1          | Row 1 Col 2        |  Row 1 Col 3    |
|  Right| $$sqrtx$$.         |     $$a_(mn)$$        |
| Row 3 Col 1          | Row 3 Col 2        |  $$(x+1)/y$$      |

Or a less cool one:
<HTML>
    <div class="wrap_round" style="width:406px; height:140px; background-
color: #505050">
    <div class="wrap_round" style="width:400px; height:135px; background-
color: #AAFFAA; color:#000000; border: 1px solid black; font-family: sans-
serif;">
    <em><center><strong>My note</strong></center></em>
    <div>
      This is my note<br>
    </div> <br></div></div>
```

```
</HTML>

===== And that's all =====

<HTML>
 <BR>
 <BR>
 <BR>
    <div class="wrap_round appear shake" style="width:406px; height:140px;
background-color: #505050">
    <div class="wrap_round" style="width:400px; height:135px; background-
color: #AAFFAA; color:#000000; border: 1px solid black; font-family: sans-
serif;">
    <em><center><strong>Bye Bye</strong></center></em>
    <div>
      This is the end<br>
    </div> <br></div></div>
</HTML>
```

From:
https://junwu.nptu.edu.tw/dokuwiki/ - **Jun Wu的教學網頁**
國立屏東大學資訊工程學系
CSIE, NPTU
Total: 339284

Permanent link:
https://junwu.nptu.edu.tw/dokuwiki/doku.php?id=dokuwiki:plugins:s5reloaded

Last update: **2021/03/28 14:51**